

## 1369

*“ePTFE/Graphite & PTFE is an excellent all-around packing compatible with most fluids”*

Combining ePTFE/Graphite with PTFE provides a packing with good heat dissipation, reduces shaft scoring, and chemical compatibility with most fluids.

1369 is an excellent all-around packing with an easy to recognize zigzag pattern.



**Construction:** Interwoven braid.

**Temperature Range:** 500°F

**pH Range:** 0-14

**Pressure:** 400 PSI

**Shaft Speed:** 1,700 FPM

**Service:** Can be used in most any general service or light slurry application.

When ordering, please specify style, size, quantity and packaging desired.

| Size   | in    | 1/8" | 3/16" | 1/4" | 5/16" | 3/8" | 7/16" | 1/2"  | 9/16" | 5/8"  | 11/16" | 3/4"  | 13/16" | 7/8"  | 15/16" | 1"    |
|--------|-------|------|-------|------|-------|------|-------|-------|-------|-------|--------|-------|--------|-------|--------|-------|
|        | mm    | 3,20 | 4,80  | 6,40 | 7,90  | 9,50 | 11,10 | 12,70 | 14,30 | 15,90 | 17,50  | 19,10 | 20,60  | 22,20 | 23,80  | 25,40 |
| Length | ft/lb |      |       |      |       |      |       |       |       |       |        |       |        |       |        |       |
|        | m/kg  |      |       |      |       |      |       |       |       |       |        |       |        |       |        |       |