

Product Data

Material:	TFE-impregnated Syn-Tex™ yarn, with Aramid corners
Construction:	Interwoven™ braid
pH Range:	2 – 12
Pressure Limit:	1500 psi (103 bar)
PV Factor:	375,000
Surface Speed:	2300 fpm (11.7 m/s)
Temperature Limit:	-10°F to 500°F (-23°C to 260°C)



Service

Style 1340 utilizes Aramid on the corners with Syn-Tex in the middle. Aramid corners provide unmatched extrusion and abrasion resistance for use in high-pressure or abrasive slurry service.

In areas where graphite cannot be tolerated style 1340 provides long noncontaminating service. If a more economical Aramid packing is required, style 1340 is the answer. Thirsty Syn-Tex holds 50 percent plus PTFE dispersion providing excellent sealability.

Typical Applications

Pumps and valves in general to abrasive conditions, e.g., slurries, salt solutions, high-pressure applications where a clean packing is required.

How to Order

Specify: style number, size, quantity and packaging desired

Size	in	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"
	mm	3,20	4,80	6,40	7,90	9,50	11,10	12,70	14,30	15,90	17,50	19,10	20,60	22,20	23,80	25,40
Length	ft/lb	N/A	N/A	23,60	15,60	11,10	7,50	6,40	5,00	4,57	3,58	2,96	2,41	2,30	2,10	1,91
	M/kg	N/A	N/A	15,80	10,50	7,44	5,02	4,29	3,35	3,06	2,40	1,98	1,62	1,54	1,41	1,28
Packaging	*Sizes 1/8" through 1/2" available in 1 lb. spools. All sizes available in 5 and 10 lb. boxes; 25 and 50 lb. reels.															