


## Product Data

Material:	PTFE-impregnated Quadrasyn™ composite containing Aramid and Kynol®
Construction:	Interwoven™ braid
PV Factor:	450,000
Surface Speed:	2200 fpm (11.2 m/s)
Temperature Limit:	-10°F to 500°F (-23°C to 260°C)
Pressure Limit:	2500 psi (172 bar)
Sealability:	Lowest clamping pressure to attain low pump leakage



## Service

Style 1392 is a general service PTFE impregnated, high performance synthetic packing. Engineered to handle a wide variety of service conditions, style 1392 is especially useful in applications including stock pumps, beaters, jordans, hydropulpers, hydrofiners, stock chests, digester pumps, sewage pumps, water pumps, mixer and agitator shafts, blenders and groove gasking.

Style 1392 is braided of our exclusive Quadrasyn™ composite containing Aramid and Kynol™, heavily impregnated with virgin PTFE dispersion and saturated with our proprietary high-temperature lubricant. Since no graphite is used in its construction, style 1392 cannot discolor fluids being pumped.

Style 1392 is recommended for general service in such fluids as air, oils, water, steam, brines and many mild to moderately reactive chemicals. (Available in rectangular cross-sections.)

## How to Order

Specify: style number, size, quantity and packaging desired

Size	in	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"	1 1/8"
	mm	3,20	4,80	6,40	7,90	9,50	11,10	12,70	14,30	15,90	17,50	19,10	20,60	22,20	23,80	25,10	—
Length (±10%)	ft/lb	76.90	36.00	21.20	14.50	10.89	7.30	6.56	4.45	3.68	3.19	2.93	2.29	1.95	1.74	1.55	1.00
	M/kg	51,69	24,10	14,25	9,70	7,20	4,80	4,39	2,99	2,47	2,14	1,96	1,54	1,31	1,17	1,04	0,67
Packaging	*Sizes 1/8" through 1/2" available in 1 lb. spools. All sizes available in 5 and 10 lb. boxes; 25 and 50 lb. reels.																