

Product Data for Style 1613

Construction:	Plaited from long-fiber, flax impregnated with TFE and lubricated to provide a flexible, formable and long-service packing.
pH Range:	6 – 9 (Brines, cold water and oils)
Temperature Limit:	-10°F to 220°F (-23°C to 104°C)
Pressure Limit:	400 psi (27.5 bar)
Shaft Speed:	2200 fpm (11 m/s)
Service:	Designed particularly for marine stern tubes, bilge pumps and rudder posts.



Product Data for Style 1600 & 1600G

Construction:	Plaited from premium grade, long-line, high tensile strength flax fiber and sealed with a superior waterproof, tallow base lubricant. (Available with a graphite coating, specify style 1600-G)
pH Range:	6 – 9 (Brines, cold water and oils)
Temperature Limit:	-10°F to 200°F (-23°C to 93°C)
Pressure Limit:	400 psi (27.5 bar)
Shaft Speed:	2200 fpm (11 m/s)
Service:	Designed particularly for marine stern tubes, bilge pumps and rudder posts.



How to Order

Specify: style number, size, quantity and packaging desired

Size	in	1/8"	3/16"	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"
	mm	3,20	4,80	6,40	7,90	9,50	11,10	12,70	14,30	15,90	17,50	19,10	20,60	22,20	23,80	25,40
1600 & 1600G	ft/lb	101,00	40,37	36,96	20,00	13,30	10,00	8,00	6,40	5,10	4,30	3,80	3,20	2,70	2,40	2,15
	M/kg	67,67	27,05	24,76	13,40	8,90	6,77	5,36	4,29	3,42	2,88	2,50	2,14	1,81	1,61	1,44
1613 Length (±10%)	ft/lb	90,48	48,00	28,00	19,00	13,00	10,00	8,00	6,10	5,40	4,50	3,70	3,20	2,90	1,25	1,20
	M/kg	68,30	32,16	18,76	12,73	8,71	6,69	5,36	4,09	3,62	3,02	2,48	2,14	1,94	0,84	0,80
Packaging	*Sizes 1/8" through 1/2" available in 1 lb. spools. All sizes available in 5 and 10 lb. boxes; 25 and 50 lb. reels.															