

Style 1347AF PTFE Impregnated Syn-Tex™

Product Data

Material:PTFE Impregnated Syn-Tex™Construction:Interwoven™ braidpH Range:2 – 12Pressure Limit:500 psi (34 bar)Shaft Speed:2300 fpm (11.7 m/s)Temperature Limit:-10°F to 450°F (-23°C to 232°C)



Service

Palmetto Syn-Tex[™], style 1347AF, is a cost-effective combination of absorbent synthetic-textile staple yarn. The "thirsty" nature of this proprietary yarn permits a 50 percent pick-up of virgin PTFE suspensoid. This protects fibers from chemical attack, reduces running friction, and enahances sealability. The material's low gland follower squeeze extends packing and sleeve life and decreases motor energy draw. The entire packing is saturated in our proprietary break-in lubricant, improving initial start-up and preventing overheating and glazing.

Style 1347AF is proven in centrifugal pumps, mixers, blenders, agitators and knife gate valves.

Features

- · Soft, flexible and thoroughly lubricated Syn-Tex extends sleeve life and reduces down time.
- · Conformable material accepts difficult environments such as shaft runout, end play or misalignment.
- · Noncontaminating/nonstaining materials prevent product rejections.
- \cdot Low initial cost reduces maintenance overhead.
- · Special petroleum-based lubricant reduces the need for adjustments during break-in periods.

How to Order

Specify: style number, size, quantity and packaging desired

Size	in	1/ ₈ "	³ /16"	¹ / ₄ "	⁵ / ₁₆ "	³ /8"	⁷ / ₁₆ "	¹ / ₂ "	⁹ / ₁₆ "	⁵ /8"	¹¹ / ₁₆ "	³ /4"	¹³ /16"	⁷ /8"	¹⁵ / ₁₆ "	1"
	mm	3,20	4,80	6,40	7,90	9,50	11,10	12,70	14,30	15,90	17,50	19,10	20,60	22,20	23,80	25,40
Length (±10%)	ft/lb	82.00	39.00	25.23	16.61	12.00	9.00	6.40	5.00	4.20	3.97	3.00	2.80	2.10	1.90	1.73
	M/kg	54,94	26,13	16,90	11,13	8,04	6,03	4,29	3,35	2,81	2,66	2,01	1,87	1,41	1,27	1,16
Packaging		*Sizes $1_{/_8}$ through $1_{/_2}$ available in 1 lb. spools. All sizes available in 5 and 10 lb. boxes; 25 and 50 lb. reels.														

Distributed by

A Greene, Tweed Company Denton Industrial Park 25 Engerman Ave., Denton, MD 21629 Phone: +1.410.479.2244, Fax: +1.410.479.0836 E-mail: info@palmettopackings.com Website: www.palmettopackings.com

Product data is based upon our experience and knowledge of typical applications and should be used to determine approximate service compatibility. All trademarks are property of their respective owners. Printed in USA ©2014 Palmetto® 08/14-GT DS-US-PI-182